



Performance Motion Devices

55 Old Bedford Rd

Lincoln, MA 01773

tel: 781.674.9860

fax: 781.674.9861

www.pmdcorp.com

Material Content Datasheet

MC1xx1A/XXCPV.x.x.G*			
Packaging Data		Package Size	24.3mm x 24.3mm
		Package Type	68-pin PLCC
		Plating / Layer Composition	NiPdAu
		Total Weight (mg)	4870
Hazmat Data	RoHS	Lead (ppm)	300
		Mercury (ppm)	ND**
		Cadmium (ppm)	ND
		Hexavalent-Chromium (ppm)	ND
		PBB (ppm)	ND
		PBDE (ppm)	ND
	Green	Bromine (ppm)	ND
		Antimony (ppm)	ND
Process Data		MSL	3 (predicted)
		Max Solder Peak Temp (Reflow) C°	260
		Max Solder Peak Duration (Reflow) Seconds	30
		Max Solder Peak Temp (Wave) C°	Not Applicable
		Max Solder Peak Duration (Wave) Seconds	Not Applicable
		Confirm IPC/JEDEC J-STD-020C (without any limitations) (JULY 2004)	Yes
		Non Magnetic Component	Yes
EOL Status		Not Recommended for new designs	
Document Rev		1.0 12/7/2005	

* R = RoHS compliant, G = Green compliant (RoHS and Sb/Br-free)
 x (lower case) = any number from 0-9
 X (upper case) = any letter from A-Z

** ND = Non-Detectable